

# Specification

## SelfCookingCenter® whiteefficiency® 201 E (20 x 1/1 GN)

**Reference number:**



**Description**

- Cooking appliance for automatically cooking (Automatic mode) meat, poultry, fish, side dishes/vegetables, egg dishes/desserts, bakery products and for automatic finishing®. With an intelligent system for optimising mixed loads in production and in à la carte service as well as a fully automatic cleaning and care system.

**Working safety**

- Detergent and Care® tabs (solid detergents) for optimum working safety
- HACCP data output and software update via integral USB port
- Safety temperature limiter for steam generator and hot-air heating
- VDE approved for unsupervised operation
- Maximum rack height 5 ¼ ft. (1.60 m)
- Integral fan impeller brake

**Operation**

- Self-teaching operation, automatically adapts to actual usage
- MyDisplay – Self-configurable, user-specific operating display (images, text, etc.)
- 8.5" TFT color monitor and touch screen with self-explanatory symbols for ease of operation
- Application and user manuals can be called up on the unit display for the current actions

**Cleaning, care and operational safety**

- Automatic cleaning and care system for cooking cabinet and steam generator works regardless of the water pressure supplied
- 7 cleaning stages for unsupervised cleaning and care - even overnight
- Automatic cleaning and descaling of the steam generator
- Automatic cleaning prompts indicating the cleaning stage and volume of chemicals in relation to the level of soiling
- Soiling and care status are displayed on the monitor
- Diagnostic system with automatic service notices displayed
- Self-Test function for actively checking unit's functions

**Features**

- Core temperature probe using 6 measuring points with automatic error correction. Positioning aid for core temperature probe included
- Climate management - humidity measured, set and regulated to one percent accuracy. Actual humidity in the cooking cabinet can be set and read on the control panel in Combi-Steamer modes
- Individual Programming of at least 350 cooking programs with up to 12 steps
- Humidification variable in 3 stages from 86°F–500°F (30°C–260°C) in hot air or combination
- USB Interface
- High-performance, fresh-steam generator with automatic descaling
- 5 fan air speeds, programmable
- Integral, maintenance-free grease extraction system with no additional grease filter
- Operation without a water softener and without additional descaling
- Separate solenoid valves for normal and soft water
- Cool-down function for fast cabinet fan cooling
- Automatic adaptation to the installation location (height, climate, etc.)
- Unit door with rear-ventilated double-glass panel and hinged inner panel
- Mobile oven rack (rail spacing 63 mm) with tandem castors, wheel diameter 125 mm
- Cooking cabinet door with integral sealing mechanism
- Material inside and out DIN 1.4301 stainless steel
- Hand shower with automatic retracting system
- Fixed waste water connection conforming to SVGW requirements where permitted
- Splash and hose-proof to IPX 5
- Demand-related energy supply
- Lengthwise loading for 1/1, 1/2, 2/3, 1/3, 2/8 GN accessories
- 5 programmable proofing stages
- Automatic, pre-selected starting time with adjustable date and time
- Handle mount for mobile oven rack

**SelfCookingControl® - 7 operating modes**



**Function - Automatic-Mode**

In the 7 operating modes, the unit's process automatically detects product-specific requirements, the size of the food to be cooked and the load size. Cooking time, temperature and the ideal cooking cabinet climate are continuously adjusted to achieve the result you want. The estimated remaining cooking time is displayed.

**Combi-Steamer mode**



Steam between 30 °C and 130 °C



Hot-air from 30 °C-300 °C



Combination of steam and hot-air  
30 °C-300 °C

**HiDensityControl®**



patented distribution of the energy in the cooking cabinet

**Efficient LevelControl® ELC®**



Mixed loads with individual rack monitoring and load-specific time adjustment for every rack

**CareControl**




Intelligent cleaning and care system

**Approval**



**Planner:**

## SelfCookingCenter® whiteefficiency® 201 E (20 x 1/1 GN)



1. Common water supply (cold water)
2. Water supply cold water / condensate "Split" water connection
3. Water supply cold / Treated "Split" water connection
4. Water drain
5. Electrical connection wire entrance
6. Chassis Ground connection
7. Steam Vent pipe DN 3" (78 mm)
8. minimum distance 2" (50 mm)
9. Measurements in mm (inch)

### Technical Info

**Lengthwise loading for:** 1/1, 1/2, 2/3, 1/3, 2/8 GN

**Capacity (GN-container/ grids):** 20 x 1/1 GN

**Number of meals per day:** 150-300

**Width:** 34 1/2 inch (879 mm)

**Depth:** 31 1/8 inch (791 mm)

**Height:** 70 1/4 inch (1.782 mm)

**Water connection (pressure hose):** 3/4" / d 1/2"

**Water pressure (flow pressure):** 150-600 kPa / 0,15-0,6 Mpa / 1,5 - 6 bar

**Water drain:** DN 50 mm

**Connected load:** 37 kW

**"Steam" connection:** 36 kW

**"Hot-air" connection:** 36 kW

**Weight (net):** 587,5 lbs (267 kg)

**Weight (gross):** 597 lbs (289,5 kg)

Mains connection	Breaker Size / (amp draw)	Cable crosssection
3 NAC 400V	3 x 63 A	5 x 10 mm <sup>2</sup>

Other voltage on request

### Installation

- The left hand clearance must be a minimum of 14" (350mm) if heat sources are affecting the left side of the unit
- Installations must comply with all local electrical, plumbing and ventilation codes

### Options

- Marine version
- Security version/prison version
- Sous-Vide core temperature probe
- Integrated fat drain
- Interface Ethernet
- Potential free contact for operation indication included
- Safety door lock
- Externally attached core temperature probe
- Mobile oven rack
- Lockable control panel
- Connection to energy optimising systems "Sicotronic" + Potential free contact for operation indication included
- Special voltages
- Unit with mobile oven rack for bakers
- Mobile with castors
- external signal unit connection

### Accessories

- GN Containers, Trays, Grids
- Thermocover
- UltraVent® Plus condensation hood with special filter technology
- UltraVent® condensation hood
- KitchenManagement System
- Heat shield for left hand side panel
- Superspike (poultry grids), CombiGrill®
- Mobile oven rack for bakers
- Special Cleaner tablets and care tabs
- Ramp for mobile oven rack
- Lamb and suckling pig spit
- Mobile plate rack
- Signal lamp